MCV Series M23 Cordsets Male Plugs with Female Thread Male Plugs with Male Threads

Face View of Male	# of Poles	Color Code		Wire AWG Rating	Length	Male Plugs (Female Threads)	Male Plugs (Male Threads)
$ \begin{array}{c} & 9 & 1 \\ & 0^8 & 0 & 10 \\ & 7 & 12 & 10 & 2 \\ & 6 & 0 & 0 \\ & 6 & 0 & 0 \\ & 5 & 0^4 \end{array} $	12	1-Brown 2-Not Used 3-Blue 4-White 5-Green 6-Yellow	7-Gray 8-Pink 9-Red 10-Black 11-Violet 12-Green/Yellow	18/3 300V 8A & 22/8 300V 4A	2 M 5 M 10 M 20 M	MCV-12MP-2M MCV-12MP-5M MCV-12MP-10M MCV-12MP-20M	MCV-12MPM-2M MCV-12MPM-5M MCV-12MPM-10M MCV-12MPM-20M
$\begin{array}{c} \begin{array}{c} \begin{array}{c} & & & \\ & & & \\ & & & \\ \end{array} \\ \begin{array}{c} & & \\ & & \\ \end{array} \\ \end{array} \\ \begin{array}{c} & & \\ \end{array} \\ \end{array} \\ \begin{array}{c} & & \\ \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} & & \\ \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} & & \\ \end{array} \\ \begin{array}{c} & & \\ \end{array} \\ \end{array}$	19	1-Violet 2-Red 3-Gray 4-Red w/ Blue 5-Green 6-Blue 7-Gray/Pink 8-White w/ Green 9-White w/ Yellow 10-White w/ Gray	11-Black 12-Green/Yellow 13-Yellow w/ Brown 14-Brown w/ Green 15-White 16-Yellow 17-Pink 18-Gray w/ Brown 19-Brown	18/3 300V 8A & 22/16 300V 4A	2 M 5 M 10 M 20 M	MCV-19MP-2M MCV-19MP-5M MCV-19MP-10M MCV-19MP-20M	MCV-19MPM-2M MCV-19MPM-5M MCV-19MPM-10M MCV-19MPM-20M

Brown, Blue and Green/Yellow are 18AWG wires.

Specifications:

Body:	Oil Resistant Yellow PUR
Contacts:	Copper Alloy with Gold Plating
Coupling Nut:	Clear Anodized Aluminum
Cable:	Oil Resistant Yellow PUR Jacket,
	Rated at 300V, 80°C, Non-Wicking,
	Non-Hygroscopic, AWM Style 20233,
	Halogen Free
	19 Pole Plug has a foil shield
Conductors:	18 AWG Bare Copper, PE Insulated
	22 AWG Bare Copper, PE Insulated
Temperature:	-40°C to +80°C (-40°F to +176°F)
Protection:	IP 67



Male Plug with Female Threads



Male Plug with Male Threads

MCV Series M23 Cordsets Female Plugs � Male - Female Extensions

Face View of Female	# of Poles	Color Code		Wire AWG Rating	Length	Female Plugs	Extension Cables
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	12	1-Brown 2-Not Used 3-Blue 4-White 5-Green 6-Yellow	7-Gray 8-Pink 9-Red 10-Black 11-Violet 12-Green/Yellow	18/3 300V 8A & 22/8 300V 4A	2 M 5 M 10 M 20 M	MCV-12FP-2M MCV-12FP-5M MCV-12FP-10M MCV-12FP-20M	MCV-12MFP-2M MCV-12MFP-5M MCV-12MFP-10M MCV-12MFP-20M
	19	1-Violet 2-Red 3-Gray 4-Red w/ Blue 5-Green 6-Blue 7-Gray/Pink 8-White w/ Green 9-White w/ Yellow 10-White w/ Gray	11-Black 12-Green/Yellow 13-Yellow w/ Brown 14-Brown w/ Green 15-White 16-Yellow 17-Pink 18-Gray w/ Brown 19-Brown	18/3 300V 8A & 22/16 300V 4A	2 M 5 M 10 M 20 M	MCV-19FP-2M MCV-19FP-5M MCV-19FP-10M MCV-19FP-20M	MCV-19MFP-2M MCV-19MFP-5M MCV-19MFP-10M MCV-19MFP-20M

Brown, Blue and Green/Yellow are 18AWG wires. For right angle cordsets, please consult the factory.

Specifications:

0000111041101101	
Body:	Oil Resistant Yellow PUR
Contacts:	Copper Alloy with Gold Plating
Coupling Nut:	Clear Anodized Aluminum
Cable:	Oil Resistant Yellow PUR Jacket,
	Rated at 300V, 80°C, Non-Wicking,
	Non-Hygroscopic, AWM Style 20233,
	Halogen Free
	19 Pole Plug has a foil shield
Conductors:	18 AWG Bare Copper, PE Insulated
	22 AWG Bare Copper, PE Insulated
Temperature:	-40°C to +80°C (-40°F to +176°F)
Protection:	IP 67



MCV Series